PLA

MATERIAL SAFTEY DATA SHEET (MSDS)

VERSION: 1.1 - 2020

PREPARED BY: STANDARD PRINT CO. www.standardprintco.com info@standardprintco.com Suite 5 / 1-5 Woodburn St Redfern, 2016, NSW

PLA Material Safety Data Sheet (MSDS)

1. Chemical Product/Manufacturer Identification

Product identifier:	Standard Print Co PLA.
Other means of identification:	Standard Print Co. uses an agent company to manufacture this filament on its behalf Polylactide resin
Use of the product:	Biodegradable resin for FDM 3D Printing
Details of manufacturer or importer:	Standard Print Company PTY LTD Suite 5, 1-5 Woodburn St, Redfern, 2016, New South Wales, Australia.
Emergency phone number:	Standard Print Co., +61 419 496 599 (Office Hours Only)

2. Hazards Identification

Classification:	Not dangerous according to Safe Work Australia's Hazardous Chemical Information System (HCIS)
Special advice on hazards:	Danger of burns in contact with hot polymer. Hazardous vapours in case of burning.

3. Composition and Information of Ingredients

Chemical characteristics:	Biodegradable polymer-blend based on polylactic acid.
CAS no:	9051-89-2

CAS no:

4. First-Aid Measures

Skin contact:	In case of contact with molten polymer immediately cool the skin with cold water. Medical aid may be required to remove adhering material and for treatment of burns.
Inhalation:	After inhalation of decomposition gases or dust remove patient to fresh air. Contact a Physician and treat symptomatically.
Ingestion:	Rinse mouth with water and drink more water. Contact a doctor in case of discomfort.

T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

Eye contact:	Rinse open eyes thoroughly with water.
5. Fire-Fighting Measures	
Auto ignition temperature:	<450°C
Extinguishing Media:	 Foam. Water. Dry chemical. For safety reasons do not use the following extinguishing agents: Carbon dioxide, Extinguishing powder. Lack of cooling capacity may permit re-ignition.
Specific Hazards under fire:	Gases Produced Upon Thermal Decomposition: • CO, HCN, AN, SM and NO In case of fire and/or explosion do not breathe fumes. Fires involving this material produce large amounts of sooty smoke; Carbon monoxide (CO) and Carbon dioxide (CO2), Hydrocarbons, Hydrogen cyanide (HCN) Under certain fire conditions, traces of other toxic gases cannot be excluded.
Specific fire-fighting measures :	Move container from fire areas if it can be done without risk. Keep personnel removed from and upwind of fire. Evacuate non-essential personnel to safe area. Fire- fighters should wear proper protective equipment and self contained breathing apparatus -MSHA/NIOSH (approved or equivalent).
Other information:	Fine particulate of the material dispersed in air may ignite. Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of dust. Apply water from a safe distance to cool and protect surrounding area.

6. Accidental Release Measures	
Personal precautions, protective equipment and emergency procedures:	Avoid dust formation and static discharge. Do not overheat material.
Measures for environmental effects:	Do not wash away into shower or waterway.
Methods and materials for containment and cleaning up:	If pellets got released in environment, take adequate steps to prevent aquatic animals and birds from eating pellets. Sweep up, place in a bag and hold for waste

Suite 5, 1-5 Woodburn St Redfern, 2016 NSW, Australia T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

	disposal. Sweep up spilled pellets on road or floor to avoid tripping.
Preventive measures for secondary accident:	Shut off all sources of ignition; No flares, smoking or flames in area.
7. Handling and Storage	
Handling:	Local ventilation / Total air ventilation : Good ventilation required when PLA is heated to a molten state.
Safety treatments:	Do not keep this material under high temperature condition for a long time. Do not touch high temperature resin PLA can generate static electricity, so take countermeasures to eliminate static electricity if necessary
Safety Measures/Incompatibility:	Do not empty into drains. Do not drop onto, or slide across sharp objects. Avoid rough handling or dropping
Recommendations for Storage:	This material is flammable. Follow fire defence and local regulations for storage and handling. Keep away from heat. Keep away from sources of ignition—No smoking. Keep away from heat source, steam pipe and direct sunlight. Store in cool (below 50°C), dry conditions in well sealed containers. Materia is hydroscopic – Keep in sealed container with desiccant or other hygroscopic substances to ensure the material remains in a dry state for optimal performance
Stability and Reactivity:	Avoid contact with Strong bases and oxidizing agents. Bio-degradable with estimated life of 5-15 years. 90 days in industrial composter Colours will fade when exposed to sun light Material integrity degrades when exposed to water and sun light.
Disposal considerations:	Does not Bioaccumulate Spools storing this product are currently non-recyclable within Australia. Dispose of unused material via registered waste carriers.

T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

2

8. Exposure Control and Persona	I Protection
Exposure limits:	No information available
Biological limit values:	Not established
Recommended monitoring procedures:	No information available
Derived no effect level (DNEL)	No information available
Appropriate Engineering measures:	When Processing, good ventilation is required to exclude dust, fumes and gases. Dust emission data not currently available
Personal protective equipment:	In case of insufficient ventilation and fume extraction, wear suitable respiratory equipment. Against powder- dust: protective mask for powder-dust Against gas from molten polymer: protective mask for organic gas
Respiratory protection:	In case of insufficient ventilation and fume extraction, wear suitable respiratory equipment. Against powder- dust: protective mask for powder-dust against gas emitted from molten polymer: protective mask for organic gas
Hand protection:	Not required (for FDM printing). Wear suitable heat- resistant gloves when handling hot or molten polymer and heated elements of the printer.
Eye protection:	Not required (for FDM printing). Wear protective eyeglasses or chemical safety goggles when handling molten filament or when post processing filament.
Skin and body protection:	Not required (for FDM printing). Wear long-sleeve clothing so as not to touch skin directly with molten filament.
Hygiene measures:	Hand in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product.
Environmental exposure controls:	Do not allow product to enter drains, water courses or soil.

9. Physical and Chemical Properties

Suite 5, 1-5 Woodburn St Redfern, 2016 NSW, Australia T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

Appearance:	Solid Filament
Density:	1.2-1.3 g/cm ³
Colour:	Variable
Odour:	Noticeable when heated
рН	Not available
Glass transition temperature:	Approx. 55°C
Boiling Point:	Not available
Melting Point:	<180°C
Decomposition Temperature:	260°C
Auto ignition temperature:	>450°C
Flashpoint:	Non-Volatile burning solid
Solubility in water:	Negligible
Solubility in other solvents:	Caustic Soda
Vapour pressure:	Not available

10. Stability and Reactivity

Reactivity:	Not reactive under normal handling conditions.
Chemical Stability:	Stable for handling under normal handling conditions.
Possibility of Hazardous reactions: Conditions to avoid:	No hazardous reactions with other chemicals known under normal handling conditions. Do not grind, pelletize or mill the material. Avoid
	temperatures above 250°C
Incompatible Materials:	Avoid water which can cause degradation of material. Material can react with strong oxidizers.
Hazardous decomposition products:	Hazardous decomposition products may form under fire conditions: carbon dioxide, acetaldehyde, carbon monoxide, nitrogen oxide may be produced.

Suite 5, 1-5 Woodburn St Redfern, 2016 NSW, Australia T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

11. Toxicological Information

Acute toxicity:	Not tested (not to be expected)
Skin corrosion/irritation: Serious eye damage/eye irritation:	Not tested (not to be expected) Not tested (not to be expected)
Respiratory or skin sensitization:	Not tested (not to be expected)
Germ cell mutagenicity:	Not tested (not to be expected)
Carcinogenic effects:	Not tested (not to be expected)
Toxicity for reproduction:	Not tested (not to be expected)
Specific Target Organ/Systemic Toxicity (Single Exposure):	Not tested (not to be expected)
Specific Target Organ/Systemic Toxicity (Repeated Exposure):	Not tested (not to be expected)
Aspiration hazards:	Not tested (not to be expected)
Others:	As for articles that are "not tested", there are no instances reported on harmful effects to health have been reported to date. Information listed in this section is transferred from safety data from the ingredients of this product.

12. Ecological Information

Aquatic toxicity:	No information
Persistence and degradability:	Minimal degradation
Bioaccumulation potential:	Does not bioaccumulate. Inherently biodegradable.
Mobility in soil:	No information
Results of PBT and vPvB assessment:	No information
Other adverse effects:	No adverse effects known to date.
Additional ecotoxicological information:	The material is practically non-soluble in water being solid. Therefore, under environmental conditions, no detrimental effects on plants, animals and micro- organism are to be expected.

13. Disposal Consideration

Suite 5, 1-5 Woodburn St Redfern, 2016 NSW, Australia T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com

PLA Material Safety Data Sheet (MSDS)

Waste treatment methods:	Dispose to an authorized waste collection point in accordance with local regulations.
Packaging:	Dispose of in accordance with local regulations.
14. Transport Information	
International transport guidelines:	Not Listed
Specific safety measures and conditions on transport:	Store in cool, dry conditions out of direct sunlight. Handle with care as to avoid damaging of outer packaging material.

15. Other Information/References

The information relates to this specific material. It may not be valid for this material, if used in combination with any other materials or in any process. It is the user's responsibility to satisfy him-selves as to the suitability and completeness of this information for his own particular use.

The information herein is given in good faith, but no warranty, express or implied, is made.

This information contained in this data sheet represents the best information currently available to us. However, no warranty is made with respect to its completeness and we assume no liability resulting from its use. It is advised to make their own tests to determinate the safety and suitability of each such product or combination for their own purposes.

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: The company does not recommend any of its products, including samples, for use: (A) in any application which is intended for any internal contact with human body fluids or body tissues (B) as a critical component in any medical device that supports or sustains human life; and (C) specifically pregnant women or in any applications designed specifically to promote or interfere with human reproduction.

Date of issue : 3/06/2019

Suite 5, 1-5 Woodburn St Redfern, 2016 NSW, Australia T: +61 419 496 599 E: info@standardprintco.com W: standardprintco.com